


P.C.B LAYOUT

L	SelfLock
NL	Nonlock



CIRCUIT DIAGRAM

SPECIFICATIONS:

- 1.RATING: 12V DC / 0.2A
- 2.CIRCUIT: 2C-2P
- 3.TIMING: NON-SHORTING
- 4.OPERATING FORCE: 250±100 gf

NO.	PARTS	MATERIALS	Q'TY	FINISH
7	CONTACT	PHOSPHOR BRONZE	1	NATURAL
6	SPRING	SUS	1	NATURAL
5	LOCK PIN	SUS	1	Ni PLATED
4	TERMINAL	BRASS	1	Ag PLATED OVER Ni
3	COVER	PPA	1	BLACK
2	CASE	PPA	1	GREY
1	KNOB	PPA	1	WHITE

东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	11/15/16			
CHECKED BY:	DATE	FINISH	MODLE	PUSH SWITCH
Jacky Chen	11/15/16			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	11/15/16	1:1		
		SHEET NO.	PART NO.	
		1 of 1		

ITEM NO	DESCRIPTION	DRAWN	DATE
1	更新材質	Jack	11/15/16

TOLERANCE UNLESS OTHERWISE STATED:	Up to 5 ±0.2	3RD. ANGEL'S	UNITS	MM
	Above 5 - 15 ±0.3			
	Above 15 - 30 ±0.4			
	Above 30 - 50 ±0.5			
	Angle ±0.3°			

SIZE	A4
VER	R1