





THICKNESS T=1.6mm
DEFAULT TOLERANCE ± 0.05



注意此母座为反脚位。



1. CURRENT RATING: 3.0A MAX
2. DIELECTRIC WITHSTAND VOLTAGE: 100VAC
3. TEMPERATURE RANGE: -30 °C ~ 85 °C
4. CONTACT RESISTANCE: 40 MILLIONHM MAX
5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
6. INSERTION FORCE :8N~35N
7. UNMATING FORCE: 8N~35N
8. DURABILITY:1500 CYCLES

X. ±0.50		X.* ±2°		UNITS mm		 東莞市高迪電子有限公司 DONGGUANGAODI ELECTRONICS CO.,LTD.											
.X ±0.30		.X* ±1°		MAT'L /		PART NO.			TITLE: IP68								
.XX ±0.10		.XX* ±0.5°															
.XXX ±0.05																	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF E-ZONE ELECTRONIC TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF E-ZONE ELECTRONIC TECHNOLOGY CO., LTD						FINISH /		APPD: RADDM			DWG NO.: USB connector						
						Q'TY /		CHKD: MARK									
								DR: JANE CHOU 2019/07/11						SCALE		SHEET	
									1/1					1/2		A	