



P.C.B LAYOUT

1. 额定负荷: 1A 250V 3A 125V AC
2. 接触阻抗: ≤50mΩ
3. 绝缘阻抗: ≥100mΩ DC500V
4. 耐焊温度: 250±5°5s
5. 使用寿命: 10,000 cycles
6. 使用温度: -25 °C to 80 °C
7. 使用湿度: ≤85% RH
8. 操作力: 450gf 可
9. 手柄长度: 2mm-10mm 可定制



东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY: Ming Ming Zou	DATE 07/23/13	MAT'L	TITLE SWITCH SERIES	
CHECKED BY: Ning Ning Su	DATE 07/23/13	FINISH	MODLE SLIDE SWITCH	
APPROVED BY: Jia Xiang	DATE 07/23/13	SCALE 1:1	DWG NO. GD-SS-H25-2211-DIP	SIZE A4
		SHEET NO. 1 of 1	PART NO.	VER R2

2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012
ITEM NO.	DESCRIPTION	DRAWN	DATE