



SUA-110M1A-30x-S277

鍍層厚度:

Blank : 1u"
2 : 15u"
3 : 30u"

RECOMMENDED PCBA LAYOUT

SPECIFICATIONS:

1.ELECTRICAL CHARACTERISTICS;

- 1.1 CONTACT RESISTANCE: 30mΩ MAX
- 1.2 DIELECTRIC WITHSTANDING VOLTAGE: 100 V 1 min
- 1.3 INSULATION RESISTANCE: 100 MΩ MIN
- 1.4 OPERATING TEMPERATURE: -25°C ~ 85°C

2.MATERIAL:

- 2.1 HOUSING: LCP
- 2.2 CONTACT: PHOSPHOR BRONZE
- 2.3 SHELL: BRASS

3.PLATING:

- 3.1 CONTACT: PLATED GOLD IN MATING AREA ;
TIN PLATED ON SOLDER BALLS ;
NICKEL UNDER PLATED OVERALL
- 3.2 SHELL: NICKEL UNDER PLATED SURFACE LAYER



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE
11/10/17
DATE
11/10/17
DATE
11/10/17

MAT'L
FINISH
SCALE
SHEET NO.

TITLE
MODLE
DWG NO.
PART NO.

CONNECTOR
USB 3.0 AF SMT 沉板3.5mm 無捲邊
SUA-110M1A-30x-S277
SUA-110M1A-30x-S277

SIZE
A4
VER
R