



HDMI-19APL2xx-S165

外殼材質：	Blank : BRASS	外殼電鍍材質：	Blank : Au
	I : SPCC		NI : Nickel

SPECIFICATIONS :

1. INSERTION FORCE : 44.1N MAX
2. WITHDRAWAL FORCE : 9.8~39.2N
3. DURABILITY : 10,000 cycles
4. CURRENT RATING : 0.5A
5. VOLTAGE RATING : 40V AC MAX
6. DIELECTNIC STRENGTH : 500V AC MIN
7. CONTACT RESISTANCE : 30 mΩ MAX
8. INSULATION RESISTANCE : 100 MΩ MIN
9. OPERATING TEMPERATURE : -25°C ~ +85°C

7	更新外殼接縫樣式	Jack	101415
6	新增PCB LAYOUT尺寸	Jack	112414
5	新增PCB LAYOUT尺寸	Jack	112014
4	更新料號及新增外殼材質和鍍層選項	Jack	111214
3	新增PCB LAYOUT	Jack	050714
2	更新圖面	Jack	030714
1	更新為A0版	Jack	011314
ITEM NO.	DESCRIPTION	DRAWN	DATE



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L		TITLE	CONNECTOR
Jack Lu	10/14/15				
CHECKED BY:	DATE	FINISH		MODLE	HDMI A TYPE 夾板公頭 板厚:1.6mm
Jacky Chen	10/14/15				
APPROVED BY:	DATE	SCALE	1 : 1	DWG NO.	HDMI-19APL2xx-S165
Tony Kao	10/14/15	SHEET NO.	1 of 1	PART NO.	HDMI-19APL2xx-S165
					SIZE A4
					VER A6