









RECOMMENDED PCB LAYOUT

Dimensional Information			
Part No.	Dimensions		
	A	B	C
4P	4.00	1.50	2.57
6P	5.00	2.50	3.57
8P	6.00	3.50	4.57



APPLICABLE FFC/FPC

Note:

1.Material

1.1: Housing: LCP, UL94-V0

1.2: Actuator: LCP, UL94-V0

1.3: Contact: Phosphor Bronze.

1.4: LEG: Phosphor Bronze.

2.Plating

2.1: Contact: Gold Plating

2.2: LEG: Matte Tin Plating Over Nickel.

3.Rating:

3.1: Operating Voltage: 50V AC/DC.

3.2: Current Rating: 0.4A AC/DC.

3.3: Contact Resistance: 30mΩ Max

3.4: Insulation Resistance: 100MΩ Min

3.5: Operating Temperature: -55°C~+85°C.



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
DATE: 01/10/19

CHECKED BY: Jacky Chen
DATE: 01/10/19

APPROVED BY: Tony Kao
DATE: 01/10/19

MATL

FINISH

SCALE

TITLE

MODLE

DWG NO.

CONNECTOR

0.5 FPC H:1.0 後掀式 0.2 CABLE 藍色蓋

FPC05L2-10xx-C3-S304

SIZE

A4

VER

PART NO.

FPC05L2-10xx-C3-S304

R4

ITEM NO.	DESCRIPTION	DRAWN	DATE
4	更新MODLE	Jack	011019
3	更新PIN選項	Jack	010919
2	更新PIN選項	Jack	120418
1	更新MODLE	Jack	080917